

Sparkweld ENGINEERING

Manufacturer of Welding Equipment

PORTABLE ROLL-SPOT WELDER



TECHNICAL SPECIFICATIONS :

MAKE	:	SPARKWELD
MODEL	:	RSW20
INPUT KVA @ 50% DUTY CYCLE	:	30 kVA
INPUT SUPPLY	:	AC400 ± 10% VOLT
PHASE	:	2 PHASE
FREQUENCY	:	50/60 Hz
NO LOAD VOLTAGE	:	12 VOLT AC
PRIMARY CURRENT	:	40 Amps.
OUTPUT CURRENT SELECTOR	:	3 STEPS
CONTROL	:	MICRO PROCESSOR BASED PROGRAMMABLE CONTROL
INSULATION CLASS	:	F
COOLING	:	FORCED AIR COOLED
SIZE (WXHXL) IN MM	:	390 X 550 X 640
WEIGHT	:	130 Kgs.

SPOT/SEAM WELDING TORCH :

MAKE	:	SPARKWELD
WELDING CABLE	:	70 sq. mm. COPPER CABLE 3 Metr. LONG WITH AIR PIPE OF DIA. 6 mm
WEIGHT (WITH CABLE)	:	5 Kgs.

OFFICE : UNIT NO. 62, FIRST FLOOR, JAGAT SATGURU INDUSTRIAL ESTATE, GOREGAON (E),
MUMBAI – 400 063, MAHARASHTRA, INDIA.

• E-mail : sparkweldengg@gmail.com • www.sparkweldengineering.com

• Phone : +91-022-49673722 • Mobile : +91-9820877054